

554,638

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
11 November 2004 (11.11.2004)

PCT

(10) International Publication Number  
**WO 2004/096524 A1**

(51) International Patent Classification<sup>7</sup>: **B29C 47/88**

(74) Agent: **MARKÓ, József**; DANUBIA Patent & Trademark Attorneys, Bajcsy-Zsilinszky 16., H-1051 Budapest (HU).

(21) International Application Number:  
PCT/HU2004/000045

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 30 April 2004 (30.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
P 0301174 30 April 2003 (30.04.2003) HU

(71) Applicant (*for all designated States except US*):  
**DR-PACK II.** [HU/HU]; Budai 10., H-2051 Biatorbágy (HU).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **PELCZ, Antal** [HU/HU]; Seregély 3., H-2040 Budaörs (HU). **ILLÉS, Tamás** [HU/HU]; Rákóczi 1., H-8913 Lakhegy (HU).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR COOLING EXTRUDED PLASTIC FOIL HOSES



(57) Abstract: This invention relates to a method for cooling extruded plastic foil hose (F), which is cooled down by driving a pressurized coolant along the internal and/or external skirt of the foil hose (F). The coolant is fed in the area of a drawing aperture (4) tangentially to the foil hose (F), and the coolant thus generated is driven as a spiral stream (16, 17) from the tangential inlet (6) to the outlet by a centrifugal force affecting the coolant along the internal and/or external surface of the foil hose (F), and by the density and pressure differences between various parts of the coolant. Said apparatus (1) comprises an internal cooling unit (1A) equipped with a distribution drum (2) provided with nozzles (13) with tangential inlets (13A). Its external cooling unit (1B) has a tangential inlet (6), which is in connection with a ring channel (G) around the foil hose (F), delimited by a tubular element (5, P).

WO 2004/096524 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*